





PERISTAR SSE - Self Priming Regenerative Monobloc Pumpsets

Get the advantages of globally trusted German technology offering unique features like die cast motor body with wide voltage range, amazing suction lift capacity, high quality bronze impeller and low maintenance cost.

KSB's widespread sales and after-market network supported by trained professionals ensure the best service all the time.

With the power of KSB Monobloc pump, you just can't go wrong.

Features:

- Stainless Steel casing and Brass impellers
- Stainless Steel shaft
- TEFC enclosure
- Self priming up to 8 m
- Dynamically balanced Rotor for longer bearing life and vibrationfree smooth operation
- Aluminium die cast body

Applications:

- Booster application
- Car washing
- Residential flats, bungalows
- Water circulation in solar systems

Operating Data:

• Pump size : 25 x 25 mm

• Capacity : up to 1400 LPH

Head : up to 24 m

Power : up to 0.37 kW (0.5 HP)

• Temperature : Ambient

• Liquid : Clear water

Technical data and selection table

Pump Model	kW (HP)	Starting Method	Pipe Size Suc x Del. (mm)	Weight approx. (kg)	Total Head in Meters						
					6	9	12	15	18	21	24
					Discharge in LPH						
PERISTAR SSE	0.37/0.5	CSR	25 x 25	8	1400	1200	1000	800	600	400	200

